

Product Data Sheet

8-3/4" M555

Design Features:

- Cast Infiltrated Tungsten Carbide matrix shell for maximum erosion and abrasion resistance.
- 3D designed and CNC machined internal steel blank for maximum blade and body strength.
- > TSP Diamond enhanced gage pads for maximum protection.
- Optimized parabolic profile for blade count, cutter quantity and bit stability.
- Force-Balanced PDC cutter locations minimize bit whirl and drill a precise round hole.
- Asymmetric blade design reduces drilling harmonics.





General Data

Part Number	2010981	981 Cutting Structure		
Body Type	Matrix Body	Face Cutters	27 @ 16mm PDC	
Gage Length	1.25 in.	Back-Up Cutters	17 @ TCI Dome	
Overall Length	15.14 in.	Gage Cutters	5 @ 16mm PDC	
Shipping Weight	149 lbs.			

Connection

Connection		Nozzie i ype	5 @ LOP Nozzie
Pin Connection	4-1/2" API Regular	TFA (min - max)	0.38 in ² to 1.53 in ²
Fishneck Diameter	5.75 in.		
Fishneck Length	4.97 in.	Recommended Operating Parameters	

Hydraulics

Make-Up Length 10.95 in. Weight on Bit (WOB) 4,000 to 20,000 lbs.

Make-Up Torque 16,500 to 18,100 ft/lbs Rotary Speed (RPM) 60 to 150 RPM